



## PRODUCT ANNOUNCEMENT

The new Edge range of street series speakers have been designed to meet the expectation of our customers. Its time to deliver the best speakers we have ever produced!

A glossy IMPP cone combined with a rubber surround allows a deep and true bass response, for a beautifully rounded sound we have paired the speakers with our unparalleled PEI tweeters.

With an ultra-slim, multi-fit basket, these are the easiest to fit Edge speakers to date! this ease fitment with our new, efficient, speaker design technology makes for a fantastic speaker.

The signature Edge orange is still a prominent feature on the street range but with a level of sophistication and aesthetic fitting its new high level of performance.

[WWW.EDGECARAUDIO.COM](http://WWW.EDGECARAUDIO.COM)



**midbass**

Tel: +44 (0)121 311 9090 [export@midbass.com](mailto:export@midbass.com)  
Midbass Distribution Ltd, Sutton Coldfield, B75 7BU, England

# EDGE

## EDST2-E6 COAXIAL SPEAKER RANGE



### ► 2 and 3 Way Coaxial Speaker

#### Configuration

#### ► PEI tweeter Element

#### ► IMPP Woofer Cone

#### ► Removeable Steel Mesh Grill \*\*\*

#### ► Multifit Design Allows Fitment

#### In 99% Of Vehicles

MODEL	EDST214-E6	EDST215-E6	EDST216-E6	EDST219-E6
TYPE	COAXIAL	COAXIAL	COAXIAL	COAXIAL
CONFIGURATION	2-WAY	2-WAY	2-WAY	2-WAY
SPEAKER SIZE	4" (100MM)	5.25" (130MM)	6.5" (165MM)	6x9" (150 x 220MM)
RMS POWER	40 WATTS	50 WATTS	60 WATTS	100 WATTS
PEAK POWER	80 WATTS	100 WATTS	120 WATTS	200 WATTS
MINIMUM INPUT (RMS)	20 WATTS	25 WATTS	30 WATTS	50 WATTS
FREQUENCY RESPONSE	100HZ - 20KHZ	80HZ - 20KHZ	65HZ - 20KHZ	45HZ - 20KHZ
IMPEDANCE	4 OHM	4 OHM	4 OHM	4 OHM
MOUNTING DEPTH	1.6" (40MM)	1.6" (41MM)	2" (50MM)	3.1" (79MM)
MOUNTING DIAMETER	3.7" (93MM)	5.5" (116MM)	5.5" (140MM)	5.7" (145MM) x 8.5" (215MM)
RECOMMENDED AMPLIFIERS	ED7300-E2 ED7600-E2	ED7300-E2 ED7600-E2	ED7300-E2 ED7600-E2	ED7300-E2 ED7600-E2

### SPECIFICATION

\*\*\* EXCLUDING EDST214-E6

MODEL	EDST214-E6	EDST215-E6	EDST216-E6	EDST219-E6
TYPE	COAXIAL	COAXIAL	COAXIAL	COAXIAL
CONFIGURATION	2-WAY	2-WAY	2-WAY	2-WAY
SPEAKER SIZE	4" (100MM)	5.25" (130MM)	6.5" (165MM)	6x9" (150 x 220MM)
RMS POWER	40 WATTS	50 WATTS	60 WATTS	100 WATTS
PEAK POWER	80 WATTS	100 WATTS	120 WATTS	200 WATTS
MINIMUM INPUT (RMS)	20 WATTS	25 WATTS	30 WATTS	50 WATTS
FREQUENCY RESPONSE	100HZ - 20KHZ	80HZ - 20KHZ	65HZ - 20KHZ	45HZ - 20KHZ
IMPEDANCE	4 OHM	4 OHM	4 OHM	4 OHM
MOUNTING DEPTH	1.6" (40MM)	1.6" (41MM)	2" (50MM)	3.1" (79MM)
MOUNTING DIAMETER	3.7" (93MM)	5.5" (116MM)	5.5" (140MM)	5.7" (145MM) x 8.5" (215MM)
RECOMMENDED AMPLIFIERS	ED7300-E2 ED7600-E2	ED7300-E2 ED7600-E2	ED7300-E2 ED7600-E2	ED7300-E2 ED7600-E2

# EDGE

## EDST2-E6 COMPONENT SPEAKER RANGE



### ► 2 Way Component Speaker

Configuration

### ► Silk Tweeter Element

### ► IMPP Woofer Cone

### ► Removeable Steel Mesh Grill

### ► Multifit Design Allows Fitment In

99% Of Vehicles

### SPECIFICATION

MODEL	EDST2150-E6	EDST216C-E6
TYPE	COMPONENT	COMPONENT
CONFIGURATION	2-WAY	2-WAY
SPEAKER SIZE	5.25" (130MM)	6.5" (165MM)
RMS POWER	60 WATTS	70 WATTS
PEAK POWER	120 WATTS	140 WATTS
MINIMUM INPUT (RMS)	30 WATTS	30 WATTS
FREQUENCY RESPONSE	80HZ - 20KHZ	65HZ - 20KHZ
IMPEDANCE	4Ω	4Ω
MOUNTING DEPTH	1.6" (41MM)	2" (50MM)
MOUNTING DIAMETER	5.5" (116MM)	5.5" (140MM)
RECOMMENDED AMPLIFIERS	ED7300-E2 ED7600-E2	ED7300-E2 ED7600-E2