



Custom tooled and stamped
EVA gasket



Dual roll foam surround
delivers high efficiency
sound reproduction.




Spade terminal allow easy
connection.



Dimpled cone incorporating
Magnus effect technology to
deliver outstanding sensitivity.



Aluminium tweeter diaphragm delivers outstanding
high frequency performance.



Model	EDBPRO36T-E1	EDBPRO37T-E0	EDBPRO6C-E3	EDBPRO6-E3	EDBPRO8-E3	EDBPRO10-E3
Type	Pro audio Tweeter	Pro Audio Tweeter	Pro Audio Coaxial	Pro Audio Midrange	Pro Audio Midrange	Pro Audio Midrange
Configuration	1-way	1-way	2-way	1-way	1-way	1-way
Speaker Size	3.8" (98mm)	3.7" (95mm)	6.5" (165mm)	6.5" (165mm)	8" (200mm)	10" (257mm)
RMS Power	80 watts	75 watts	150 watts	150 watts	175 watts	200 watts
Peak Power	160 watts	150 watts	300 watts	300 watts	350 watts	400 watts
Sensitivity	103dB	102dB	98dB	98dB	98dB	99dB
Frequency Response	2kHz - 20kHz	2kHz - 20kHz	125Hz - 10.5kHz	125Hz - 10.5kHz	100Hz - 9kHz	70Hz - 8.5kHz
Impedance	4 Ohms	4 Ohms	4 Ohms	4 Ohms	4 Ohms	4 Ohms
Mounting Depth	1.5" (39mm)	1.1" (28mm)	3" (75mm)	3" (75mm)	3.3" (85mm)	4.1" (103mm)
Mounting Diameter	3.1" (80mm)	2.9" (73mm)	5.7" (145mm)	5.7" (145mm)	7.3" (186mm)	9.3" (237mm)

